Dwyer. **SERIES A1PS/A1VS ECONOMICAL PRESSURE SWITCH** Vacuum and Compound Ranges Available, Adjustable Set Point



The Series A1PS/A1VS Economical Pressure Switch is designed with a 15 Amp SPDT switch for direct control of pumps and motors. Available in pressure, vacuum, or compound ranges, the switches offer a field adjustable set point. Easily adjust the switch by aligning the top of the self locking adjusting nut with the desired setting indicated on the adjustable. Connection is 1/4 ^r male NET for quick
indicated on the adjacent range scale. Connection is 1/4" male NPT for quick installation and can be mounted in any position.

FEATURES/BENEFITS

- 15 A contact allows direct control reducing costs and reliability by having to introduce additional contacts and relays

 Field adjustable reduces installation time bring application on-line faster

APPLICATIONS

- OEM Compressors Motor control
- Process equipment
 Pump control

SPECIFICATIONS							
Service: Compatible liquids or gases. Wetted Materials: Diaphragm: Buna-N; Body with fitting: Zinc alloy, chromate finish. Temperature Limits: -31 to 185°F (-35 to 85°C). Pressure Limits: 600 psig. Vacuum Limits: 29.9° Hg (vacuum and compound models only). Switch Type: SPDT snap action.	Electrical Ratings: 15 A (resistive) @ 250 VAC, 1/2 HP @ 250 VAC. Electrical Connections: Three screw terminals. Process Connection: 1/4" male NPT. Set Point: Field adjustable via knurled screw cap. Cycling: Not to exceed 1 Hz. Sensor Element: Diaphragm. Weight: 7.4 oz (209 g). Agency Approvals: UL.						

1/4 NP

MODEL CHART									
	Set Point Range (kPa)	Repeatability (kPa)	Deadband (approx.) (kPa)		Set Point Range (kPa)	Repeatability (kPa)	Deadband (approx.) (kPa)		
A1PS-24 A1PS-34		±1.0 psi (7) ±5.0 psi (34)	2 to 5 psi (14 to 34) 5 to 30 psi (34 to 207)	A1VS-24	28" Hg to 3.5 psig (-94 to 24)	±1.2″ Hg (-4) ±1.2″ Hg (-4), ±0.15 psi (1)	3-14″ Hg (-10 to -47) 6″ Hg - 1.5 psi (-20 to 10)		

2.375 [60.33] \otimes θ \otimes 3.625 [92.08] Ø1.625 [41.28]

LISTED