

Application Spotlight

# Low Emission Glass Manufacturing (Low-E)

# Improved Repeatability & Plug-and-play Functionality

## Low Emission Glass Manufacturing (Low-E)

Low-E glass incorporates multiple layers of metal or other compounds as a surface coating that provides high transmittance for visible lights and high reflectance for mid-IR and far-IR lights. The coating benefits are excellent heat insulation and favorable light transmission compared to standard and traditional-coated glass used in the building industry.




Fig. 1 Functional process scheme of a plasma glass production

### Application

In Low-E glass manufacturing, vacuum magnetron sputtering is a common coating technique used across the globe. In this process, gas flow (inert gas Ar or reactive gas  $O_2$  and  $N_2$ ) in the vacuum environment must be controlled with a top-quality mass flow controller (MFC) to maintain a stable vacuum level.

With the magnetron target acting as the cathode, a high voltage provided by an AC or DC power supply will ionize process gas to generate plasma. Electrons move at high speed under the joint force of the electric field and magnetic field, colliding with gas molecules and creating more positive ions and electrons.

After gaining a certain energy, positive ions in the electric field will hit the cathode target material. The sputtered target material deposits on the glass substrate to form thin films. Uniform and consistent film layers are required.




Fig. 2 Eight Vögtlin Mass Flow Controllers (MFCs) in a compact unit. Includes integrated solenoids and manual shut-off valves. Due to an intelligent design concept without screws, the MFCs can be quickly installed and removed. This enables a fast replacement of devices.

## Challenge

Inflow gas should be maintained at a very stable level in the coating process to avoid uneven coating and significant spots and negatively impacting the general energy of particles in the coating, which is not favorable for reactive deposition. A complicated gas distribution system requires numerous of process gas branches. Installation and commissioning of single channel gas circuits are tedious with heavy work load. In addition, this system typically reduces efficiency, and generates multiple leakage points. Human operation errors (wrong connection of gas mixing and connection circuits) also can negatively impact operations.



Fig. 3 **Vögtlin offers modular MFC systems based on your demands and requirements.**

## Solution

MEMS technique of the MFCs provides for a 350ms rapid response. Plug-and-play functionality and no warm-up periods improve user productivity.

*Vögtlin Mass Flow Controllers* have a unique way of compensating for changes in ambient and gas temperature, which strongly improves the repeatability. The MEMS technology insures a long-term stability without any drift as long as the gas supply is clean and dry. Only one bolt is required to fix an MFC, allowing faster and more accurate removal/assembly.

An Integrated valve bank design and accurate internal mixing and distribution pipe design help avoid operational risks and improve end user comfort. Other benefits include saving of consumables for gas source pipes, reduced leakages points and field installation time as well as an easy and accurate realization of complicated gas mixing and distribution process.

Units can be calibrated for multiple gases and parameters, which leads to significant reductions in spare part inventories and cost savings.

## Key Features

- ★ High repeatability & reliability
- ★ Short response time
- ★ Safe and fast control
- ★ Compact unit with high-quality components

## Interfaces

- ★ Analog
- ★ Modbus RTU
- ★ Profibus DP-V0/DP-V1
- ★ Profinet\*
- ★ EtherCAT\*

\*available from January 2019

## About Vögtlin Instruments GmbH

Established in 1986, Vögtlin Instruments GmbH is a Swiss designer of precision flow instrumentation. Vögtlin became a member of the TASI group in 2011. The division TASI Flow delivers flow meter, flow control and dispensing solutions. TASI Flow products are developed, customized and serviced through technical centers in the US (Wisconsin), in Europe (Germany, Switzerland and the UK) and China (Beijing and Shanghai).

» [www.voegtlin.com](http://www.voegtlin.com)



## Worldwide TASI Flow Network



Vögtlin Sales & Service Hub North America:

**AW-Lake Company**

2440 W. Corporate Preserve Dr. #600  
Oak Creek, WI 53154, USA

Phone +1 414 574 4300

Fax +1 414 574 4301

info@aw-lake.com

[www.aw-lake.com](http://www.aw-lake.com)

International Headquarter:

**Vögtlin Instruments GmbH**

Langenhagstrasse 1  
4147 Aesch BL, Switzerland

Phone +41 61 756 63 00

Fax +41 61 756 63 01

info@voegtlin.com

[www.voegtlin.com](http://www.voegtlin.com)

Vögtlin Sales & Service Hub China:

**KEM flow technology (Beijing) Co., Ltd.**

Rm. 906, Block C, RuiPu Office Bldg,  
No. 15, HongJunYingNan Road,  
Chaoyang District, Beijing 100012, China

Phone +86 10 849 29567

info@kem-kueppers.cn

[www.voegtlin.cn](http://www.voegtlin.cn)

Find your local Vögtlin sales partner on our website:

[www.voegtlin.com](http://www.voegtlin.com)



**Vögtlin Instruments GmbH – gas flow technology**

Langenhagstrasse 1 | 4147 Aesch (Switzerland)

Phone +41 61 756 63 00 | Fax +41 61 756 63 01

[www.voegtlin.com](http://www.voegtlin.com) | [info@voegtlin.com](mailto:info@voegtlin.com)

**vögtlin**   
instruments